



TOBY BREWER
CHIEF DAM SAFETY ENGINEER

MAY 17, 2016



AGENDA

- > TACOMA POWER'S PROJECTS
- > CUSHMAN PROJECT
- > OVERVIEW OF DRUM GATE PAINTING PROJECT
- > PHOTOS
- > LESSONS LEARNED
- > QUESTIONS



PROJECT LOCATIONS







CUSHMAN NO. 1
DAM

- > Year Constructed: 1926
- Height: 275 feet
- > Width: 1,111 feet
- Reservoir Length: 9.6 miles
- Reservoir Volume: 453,350 ac-ft





CUSHMAN PROJECT



CUSHMAN NO. 2
DAM

Year Constructed: 1930

Height: 235 feet

Width: 575 feet

Reservoir Length: 2 miles

Reservoir Volume: 8,000 ac-ft







> DRUM GATES

- Number of Gates: 3
- > Length: 40 feet
- > Height: 19 feet
- > Width: 15.7 feet
- Weight: 100,000 pounds










- > HOW DO WE REPAINT THE END PLATES OF DRUMS?
 - > 9-inches of Clearance to Piers
- TWO VIABLE OPTIONS
 - Lift the Gates Up Above the Piers
 - Roll the Gates Out on to the Spillway Apron








'NORMAL-UP' POSITION















HYDRAULIC RAM INSTALLATION




























CONCEPTUAL DIAGRAM
NOT TO SCALE



































































- LESSONS LEARNED
 - > Include Stripe Coat of Paint Around Rivet Heads and Seams
 - Install Cathodic Protection Anodes if Possible
 - MC-Tar Is Not UV Stable
 - Side and Corner Seals Continue to Leak
 - Document and Retain Maintenance Plans for the Future
 - Plan for Future Maintenance in the Initial Designs



QUESTIONS?

